

Claims:

1. A method for controlling transmission power in a radio system having a transmitting end and a receiving end, the method comprising the steps of

- 5 - transmitting a digital signal from the transmitting end to the receiving end,
 - receiving said digital signal at the receiving end,
 - monitoring signal quality at the receiving end, and
 - adjusting the transmission power at the transmission end in
10 accordance with the monitored signal quality, said monitoring and adjusting being characterized by the further steps of
 - monitoring pseudo error occurrence at the receiving end,
 - decreasing the transmission power when the rate of the pseudo errors is below a predetermined threshold, and
15 - increasing the transmission power when pseudo errors occur so that a predetermined condition is fulfilled.

2. A method as claimed in claim 1, characterized in that the transmission power is increased immediately when a pseudo error is detected.

3. A method as claimed in claim 1, characterized in that the
20 transmission power is decreased in small steps for a predetermined time period at each step.

4. A method as claimed in claim 2 or 3, characterized by
 (a) adjusting the transmission power after the set-up of the radio system to a value high enough so that no pseudo errors are detected at the
25 receiving end,
 (b) decreasing the transmission power until the first pseudo error is detected,
 (c) increasing the transmission power in response to the pseudo error detected, and
30 (d) jumping to phase (b) if no pseudo errors are detected during a predetermined time period after the transmission power has been increased in phase (c).

5. A method as claimed in claim 1, characterized in that the
35 transmission power is increased by a small predetermined amount when said pseudo errors are detected.

6. A method as claimed in claim 1, characterized by
- using forward error correction (FEC) in the transmitted signal,
- decoding the signal at the receiving end by means of a FEC
decoder, and

5 - interpreting the corrections made by the decoder as pseudo errors.

7. A method as claimed in claim 1, characterized by using at
the receiving end a demodulator provided with a first set of thresholds for
making a decision on a received symbol and a second set of thresholds for
making a decision on whether a pseudo error has occurred.

10 8. A method as claimed in claim 1, characterized by the
further steps of

- monitoring the rate of actual errors at the receiving end, and
- increasing the transmission power temporarily to the maximum
transmission power when a predetermined error rate threshold is exceeded.

15 9. A radio system including

- at a receiving end first means (SMA, SMB, 15a, 15b) for monitoring
signal quality and for producing a control signal on the basis of the monitored
signal quality, and

- at a transmitting end second means (15a, 15b) for adjusting the
20 transmission power in response to said control signal,
characterized by

said first means being adapted to monitor the occurrence of pseudo
errors and to produce a control signal indicating when the pseudo errors are
detected and when the rate of the pseudo errors is below a predetermined
25 threshold, whereby said second means are responsive to said control signal
by increasing the transmission power when the pseudo errors are detected
and by decreasing the transmission power when the rate of the pseudo errors
is below a predetermined threshold.

10. A radio system as claimed in claim 9, characterized in
30 that said first means include a FEC decoder (45) for decoding a FEC coded
signal and for detecting pseudo errors.

11. A radio system as claimed in claim 9, characterized in
that said first means include a demodulator provided with a first set of
thresholds for making a decision on a received symbol and a second set of
35 thresholds for making a decision on whether a pseudo error has occurred.